

## Cross-Reference Guide - Model 7505

### Features & Benefits

- Thermostat and boiler control compatible
- Programmable valve-on delay and motor-off delay
- Three status lights for system monitoring and diagnostics
- Welded relay protection with redundant motor relays
- Limited reset and limited recycle
- Sleek, modern design
- Technician Pump Prime mode
- 5-Year Warranty
- Two communication ports for adding alarm contacts, programming display, and/or future wireless communications



Manufacturer	Model	Lockout	Pre*	Post**	Beckett GeniSys Recommended Replacement
Carlin	40200-02	15	0	0	7505A-0000
Carlin	42230-02	30	0	0	7505A-0000
Carlin	48245 (Intermittent Ignition)	45	0	0	7505A-0000
Carlin	50200-02	15	0	0	7505A-0000 (+ 52040 Alarm Module)
Carlin	60200-02	15	10	10	7505P-1515 (+ 52040 Alarm Module)
Honeywell	R7184A1000 R7184A1026 R7184A1075	15	0	0	7505A-0000
Honeywell	R7184A1018 R7184A1034				7505A-0000
Honeywell	R7184A1042	45	0	0	7505A-0000
Honeywell	R7184B1016 R7184B1024 R7184B1032	15	15	0	7505B-1500
Honeywell	R7184P1080	15	15	15	7505P-1515
Honeywell	R7184P1056 R7184P1064	15	15	selectable	7505P-1515
Honeywell	R7184P1049 R7184P1072 R7184U1004	15	0/15	selectable	7505P-152M (+ 52040 Alarm Module)
Honeywell	R7184U1012	30	0/15	selectable	7505P-152M (+ 52040 Alarm Module)

Continued on back ►

## Cross-Reference Guide - Model 7505

◀ Continued from front

Manufacturer	Model	Lockout	Pre*	Post**	Beckett GeniSys Recommended Replacement
Honeywell	R7184U1020	45	0/15	selectable	7505P-152M (+ 52040 Alarm Module)
Honeywell	R8184G (Intermittent Ignition)	15, 30, or 45	0	0	7505A-0000
Honeywell	R8184P (Intermittent Ignition)	15 or 45	15	4 min.	7505P-152M
Honeywell	R8184M (Intermittent Ignition)	45	0	0	7505A-0000 (+ 51950 A/C Ready Kit)
White-Rogers	668-364 668-601	15	0	0	7505A-0000
White-Rogers	668-264 668-501	30	0	0	7505A-0000
White-Rogers	668-401 668-430	45	0	0	7505A-0000
White-Rogers	668-451	45	0	0	7505A-0000 (+ 51950 A/C Ready Kit)

All Beckett recommended controls are interrupted duty ignition controls with a 15 second safety lockout, limited recycle, limited reset, communication ports, diagnostic LEDs and ambient temperature range from -40°F to +150°F.

For replacement information concerning controls not listed above, contact your Beckett sales representative or call our technical service department at: 1-800-OIL BURN (1-800-645-2876) 8AM to 5PM EST, Monday thru Friday.

\* The pre (valve on delay) timing on all GeniSys controls can be reprogrammed by the GeniSys display.

\*\* The post (motor off delay) timing on all GeniSys controls can be reprogrammed by the GeniSys display.



◀ GeniSys Control shown with 52067 GeniSys Display and 52040 Alarm module

R.W. BECKETT CORPORATION

USA: R.W. Beckett Corporation • ph: (800)645-2876 • fax: (440)327-1064 | Canada: R.W. Beckett Canada Ltd. • ph: (800)665-6972 • fax: (519)763-5656

[www.beckettcorp.com](http://www.beckettcorp.com)