

7610



it's the little things that make a **BIG DIFFERENCE**








- Expanded Wiring Area Almost twice the room for wiring and conduit connectors.
- LWCO Status on Display LWCO: ON = LWO is working LWCO: OFF = LWCO disabled LWCO: NA = Temp only sensor
- **On/Off Switch** Can be placed in any knockout.
- Improved Knockouts Easier to remove and better a aligned with bracket.
- NEW Grounding Options Repositioned terminal plus a second terminal for easy access.
- Redesigned Well Mounting For straight mounting on 3/4" and 1/2" wells.
- Economizing Display Alternates with status display anytime Heat Manager is active. Displays current economized setpoint.
- LCD Display Backlight Display will now stay on for four hours when a button is pressed.







Add the 7622TW Brass Well for even more improvements



Machined brass bodies for strength and consistent threads

7622TW Brass Thermowell 3/4" NPT

Wells Tested to 250 F and 250 PSI

Ordering Information: Contact Customer Service at 1-800-645-2876

Part Number	Description
7610A0001U	AquaSmart Boiler Temperature Control - 120Vac - Oil with Temperature ONLY Sensor (120 Vac burner circuit)
7610B0001U	AquaSmart Boiler Temperature Control - 120Vac - Gas with Temperature ONLY Sensor (24 Vac burner circuit)
7610A000LU	AquaSmart Boiler Temperature Control - 120Vac - Oil LESS Sensor (120 Vac burner circuit)
7610B000LU	AquaSmart Boiler Temperature Control - 120Vac - Gas LESS Sensor (24 Vac burner circuit)
7600TSU	Replacement Temperature Only Sensor Unit Pack
7600P01U	Replacement Temperature / LWCO Sensor Unit Pack
7622TW01	Brass Immersion Well - 2 - 3/16" Insulation Depth and 1/8" Insertion Depth
7622TW02	Brass Immersion Well - 2 - 3/16" Insulation Depth and 1%" Insertion Depth
7622TW03	Brass Immersion Well - 31/2" Insulation Depth and 15/8" Insertion Depth
7622TW04	Brass Immersion Well - 4¾ Insulation Depth and 15/8 Insertion Depth
7600RMU	48" AquaSmart Remote Mount Kit
7600WTMU	Wireless Temperature Module for Outdoor Reset

